

此告示已由劳工处处长批准，并须根据
工厂及工业经营(砂轮)规例第 14 条所规定而张贴

This warning notice has been approved by the Commissioner for Labour
and must be posted for the purpose of Regulation 14 of the Factories and
Industrial Undertakings (Abrasive Wheels) Regulations

使用砂轮时 应注意下列

WARNING NOTICE WHEN USING ABRASIVE WHEELS

危險

(1) 砂轮爆裂之原因：

砂轮之内在损坏

超速转动

错误嵌固

使用不当

(2) 嵌固轮子与端点之破裂

(3) 与砂轮接触

(4) 飞扬之微粒引致眼部受伤

安全预防措施

用敲击试验办法，检查砂轮之
完整无疵。

依照砂轮制造商之指示，
不可超越最高容许转速。




砂轮须由一位书面指定及曾
受训练之合资格的人嵌固。

勿用过大压力。
当使用直边砂轮作侧面打磨时，
应特别小心。

勿超越制造商所指定之外露轴段。
心轴应固定在夹头内。

使用：护罩，枕件，防护屏障
(或护眼用具)。

砂轮须妥善修正和整修。



DANGERS

(1) Bursting of wheel, due to :

Latent defect of wheel

Overspeeding

Faulty mounting

Misuse by operator

(2) Fractures of mounted wheels and points

(3) Contact with wheel

(4) Eye injuries from flying particles

SAFETY PRECAUTIONS

Check soundness of wheel by ring test.

Do not exceed maximum
permissible speed of wheel as
specified by manufacturer.

The wheel must be mounted by
a trained and competent person
appointed in writing.

Never use excessive pressure
on the wheel.
Use particular care when grinding
on the side of a straight-sided wheel.

The overhang not to exceed that is
permissible by the manufacturer.
The mandrel to be secured properly
in the collet of chuck.

Use : Wheel guards, work-rest,
protective screen
(or eye protectors).

Wheels must be properly trued
and dressed.

