

此告示已由勞工處處長批准，並須根據
工廠及工業經營(砂輪)規例第 14 條所規定而張貼

This warning notice has been approved by the Commissioner for Labour
and must be posted for the purpose of Regulation 14 of the Factories and
Industrial Undertakings (Abrasive Wheels) Regulations

使用砂輪時 應注意下列

WARNING NOTICE WHEN USING ABRASIVE WHEELS

危險

(1) 砂輪爆裂之原因：

砂輪之內在損壞

超速轉動

錯誤嵌固

使用不當

(2) 嵌固輪子與端點之破裂

(3) 與砂輪接觸

(4) 飛揚之微粒引致眼部受傷

安全預防措施

用敲鳴試驗辦法，檢查砂輪之
完整無疵。

依照砂輪製造商之指示，
不可超過最高容許轉速。

砂輪須由一位書面指定及曾
受訓練之合資格的人嵌固。




勿用過大壓力。

當使用直邊砂輪作側面打磨時，
應特別小心。

勿超越製造商所指定之外露軸段。
心軸應固定在夾頭內。

使用：護罩，枕件，防護屏障
(或護眼用具)。

砂輪須妥善修正和整修。



DANGERS

(1) Bursting of wheel, due to :

Latent defect of wheel

Overspeeding

Faulty mounting

Misuse by operator

(2) Fractures of mounted wheels and points

(3) Contact with wheel

(4) Eye injuries from flying particles

SAFETY PRECAUTIONS

Check soundness of wheel by ring test.

Do not exceed maximum
permissible speed of wheel as
specified by manufacturer.

The wheel must be mounted by
a trained and competent person
appointed in writing.

Never use excessive pressure
on the wheel.
Use particular care when grinding
on the side of a straight-sided wheel.

The overhang not to exceed that is
permissible by the manufacturer.
The mandrel to be secured properly
in the collet of chuck.

Use : Wheel guards, work-rest,
protective screen
(or eye protectors).

Wheels must be properly trued
and dressed.

