


As far as practicable, the truss-out bamboo scaffold should be designed/ certified by a professional engineer. If not, the contractor must take the following interim safety measures:

When working on a truss-out bamboo scaffold, it is necessary to make available an independent lifeline for each worker and provide workers with safety harnesses. Effective measures should also be taken to ensure that the workers wear the safety harnesses and attach them to independent lifelines with fall arrestors when working on the scaffold.

5



6

Other Relevant Publications

1. Code of Practice for Bamboo Scaffolding Safety
2. Safety Hints on Truss-out Bamboo Scaffolding (Chinese version only)
3. Guidance Notes to Renovation Safety
4. A Guide to the Provisions for Safe Places of Work under Part VA of the Construction Sites (Safety) Regulations
5. Guidance Notes on Classification and Use of Safety Belts and their Anchorage Systems

Enquiries

If you wish to enquire about this Guide or require advice on occupational safety and health matters, please contact the Occupational Safety and Health Branch of the Labour Department through:

Telephone: 2559 2297 (auto-recording service available outside office hours)
 Fax : 2915 1410
 E-mail : enquiry@labour.gov.hk

Information on the services offered by the Labour Department and on major labour legislation is also available on our website at <http://www.labour.gov.hk>.

For details on the services offered by the Occupational Safety and Health Council, please call 2739 9000.

Complaints

If you have any complaints about unsafe workplaces and work practice, please call the Labour Department's occupational safety and health complaint hotline at 2542 2172. All complaints will be treated in the strictest confidence.

7

Safety Measures for Use of Truss-out Bamboo Scaffold



1



3

4